



# Specifications O<sup>2D</sup>S Z Scanners



Models :	O <sup>2D</sup> S 250	O <sup>2D</sup> S 325	O <sup>2D</sup> S 450	O <sup>2D</sup> S 750	O <sup>2D</sup> S 505	O <sup>2D</sup> S 1155	O <sup>2D</sup> S 1950	O <sup>2D</sup> S 1350
<b>Measurement data:</b>								
Radial distance from mirror axis	200-300 mm	200-450 mm	200-700 mm	400-1100 mm	450-550 mm	1000-1300 mm	1500-2400 mm	700-2000 mm
Minimum 10° scan arch	± 5°	± 5°	± 5°	± 5°	± 5°	± 5°	± 5°	± 5°
Depth of Field (X)	98 mm	248 mm	497 mm	695 mm	98 mm	295 mm	890 mm	1292 mm
Field of View close end (Y)	35 mm	35 mm	35 mm	70 mm	79 mm	175 mm	262 mm	123 mm
Field of View far end (Y)	52 mm	78 mm	121 mm	191 mm	95 mm	226 mm	418 mm	348 mm
Maximum 50° scan arch	± 25°	± 25°	± 25°	± 25°	± 25°	± 25°	± 25°	± 25°
Depth of Field (X)	72 mm	207 mm	434 mm	597 mm	48 mm	178 mm	675 mm	1113 mm
Field of View close end (Y)	186 mm	186 mm	186 mm	372 mm	419 mm	932 mm	1398 mm	652 mm
Field of View far end (Y)	253 mm	379 mm	591 mm	928 mm	464 mm	1098 mm	2028 mm	1688 mm
Radial / Polar Resolution	0.03 mm	0.05 mm	0.1 mm	0.2 mm	0.05 mm	0.2 mm	0.6 mm	0.8 mm
Radial / Polar Reproducibility	± 0.03 mm	± 0.05 mm	± 0.1mm	± 0.2 mm	± 0.05 mm	± 0.2 mm	± 0.6 mm	± 0.8 mm
Radial / Polar Linearity	± 0.10 mm	± 0.20 mm	± 0.2 mm	± 0.4 mm	± 0.10 mm	± 0.5 mm	± 1.2 mm	± 1.6 mm
Size of spot	Ø 1 mm	Ø 2 mm	Ø 3 mm	Ø 3 mm	Ø 1 mm	Ø 1 mm	Ø 2 mm	Ø 3 mm
Laser protection class: 2 / 6 kHz	IEC 2 / IEC 2	IEC 2 / IEC 2	IEC 2 / IEC 3R	IEC 2 / IEC 3R	IEC 2 / IEC 3R	IEC 3R / IEC 3B	IEC 3R / IEC 3B	IEC 3R / IEC 3B

\*) Static measurement on white paper without any averaging of the output signals, sampling and output frequency being equal.

### Common Measurement data:

Updating frequency	2000 Hz or 6000 Hz
Scan rate (from one side to the other for 2 kHz model)	600 or 300 scans/min.
Angular resolution at Minimum 10° scan arch (2 kHz)	< 0.08° or < 0.04°
Angular resolution at Maximum 50° scan arch (2 kHz)	< 0.4° or < 0.2°
Scan rate (from one side to the other for 6 kHz model)	1800, 900 or 450 scans/min.
Angular resolution at Minimum 10° scan arch (6 kHz)	< 0.08° < 0.04° or < 0.02°
Angular resolution at Maximum 50° scan arch (6 kHz)	< 0.4° < 0.2° or < 0.1°
Temperature deviation	± 0.03% FS/C°
Light source ( nm )	Laser (655)

### Electrical data:

Serial output : 2 kHz / 6 kHz	RS232 or RS422 / RS422
Baud rate : 2 kHz / 6 kHz	115200 / 230400
Supply voltage	22 - 36 VDC
Power consumption	max 12 W

### Environment data:

Operating temperature	0 - +45 C°
Storage temperature	-20 - +70 C°
Humidity non condensing	Max 90 % RH
Degree of protection	IEC IP65
Operating temperature	0 - +45 C°

### Physical data:

Dimensions	310 x 190 x 64 mm
Weight excl. Cable	4.5 kg
Cable length	2.5 m
Housing	Aluminum & Glass windows

Distributor and System Integrator




**IFELL Laser & Sistemi s.r.l.**

v. dei Ronchi 51/A1  
10091 Alpignano TO Italy  
tel. (+39) 011 9664240  
info@ifell.it www.ifell.it


## General Description

The O<sup>2D</sup>S Z scanner is an optical measuring device for non-contact precision measurement in two dimensions. The measurement is performed by oscillating the triangulation plane over X° up to 5 0°. A fine collimated or focused laser beam is diffusely reflected from the surface of almost any kind of material or fluid, and a CCD-camera records the image through an objective. This makes it possible for a Digital Signal Processor to calculate the (radial) distance from the centre of the mirror axis to the object surface, as well as keeping track of the angular reference position.

The O<sup>2D</sup>S measuring system is a compact unit where optics, CCD-camera, and digital signal processing electronics all are integrated in the sensor housing. The schematic drawing to the right shows the scanner seen from the side. It is here indicated, with this orientation of the scanner, how the triangulation plane can sweep from minus 25° below the horizontal plane to plus 25° above the horizontal plane. The measured distance data is available with a measuring frequency of 2 or 6 kHz as a digital signal for an application running under Windows and using the O<sup>2D</sup>S driver DLL. The scanner is delivered with CD's containing the mentioned DLL and a Windows test/demo program. The PC application program receives output data from the scanner over the RS422/RS232 serial interface and a COM port via the DLL. The software either converts polar coordinates of a measurement point to orthogonal X, Y-coordinates or presents a profile (table of X, Y-values) for each sweep from one side to the other. Within the application program the user can specify the size of the Y-increment and thus the length of the output table containing the profile data. Standard Models of the O<sup>2D</sup>S scanner can be delivered in 8 different measuring ranges, and each in two versions with different measuring angles, either 10° or 50° and then in 2 or



## Dimensions



3 scan rates giving high or low angular resolution, and can furthermore be customized to other than standard scan angles and measuring ranges.

## Multi O2DS applications

The O<sup>2D</sup>S scanners are also available in a synchronized version, where the units are programmed to operate as either a SLAVE unit or as a MASTER unit controlling one or more SLAVE units.

## High Target Temperature

The O<sup>2D</sup>S scanners are also available in pHigh target Temperature and high Laser light intensity versions, and a 2 kHz model in HT form can take care of applications with surface temperatures up to 1000°C as a IEC 2 laser class scanner. In VHT IEC 3R form it can handle up to 1300°C, and in VVHT form with **BLUE** laser diode it will take care of over 2000°C hot target surfaces.